

SPECIFICATION

Model	PK4-5600	PK4-5600(S)	PK5-5600	PK6-5600	PK6-5600(A)
Dimension(mm)	6.5x10.4x2.5	6.5x10.4x2.5	6.5x10.4x2.5	6.5x10.4x2.5	6.5x10.4x2.5
Weight(grams)	120	120	120	120	120
Supports	V.90, V.92	V.90, V.92	V.90, V.92	V.90, V.92	V.90, V.92
Chipset	Conexant	Conexant	Topic	Conexant	Conexant
SurgeProtection	2kV	10kV	2kV	2kV	10kV

FEATURES

Serial RS-232 connection

Works with Palm, PSION, Pocket PC, PCs, Notebooks, MACs, WinCE, etc.

56K* V.90/V.92

Data/Fax/Voice Modem

Optional re-chargable NI-MH battery-pack

Compact size and weight

2 MB Flash ROM

1- year warranty

TECHNICAL INFORMATION

External COM device PnP Support

Line quality monitoring and auto retrain

NVRAM directory and stored profiles

Flow control and speed buffering

Automatic format/speed sensing

Serial asynchronous data

Auto dial and auto answer

Tone and pulse dialing

Build-in speakerphone

Selectable operating modes

Data mode

Throughput

up to 115.2Kbps

V.90, V.34, V.32bis, V.22bis, V.22A/B, V.23 and V.21 Bell 212A and 103

V.42 LAPM MNP 2-4 and MNP 10 error corrections

V.42bis MNP5 data compression

Fax Mode

Send/receive rates up to 14.4 Kbps

V.17, V.29, V.27ter and V.21 channel 2

AT, fax class 1 commands

S registers

Built-in DTE interfaces

DTE speed up to 115.2Kbps

Serial ITU-T V.24 (EIA/TIA-232-E)

Full-duplex speakerphone with acoustic and line echo cancellation

Room monitor

Utilizes 5V DC Power, and 300mA**APPROVALS**

FCC (Part 15 Class B /Part 68)

CE

*Actual speeds over U.S. telephone lines vary and are less than 56Kbps due to current FCC regulations and line conditions.